Bowers & Wilkins





Wolf in sheep's clothing

It might have a more traditional appearance than other speakers in the range, but don't let that fool you. The 804 D3 delivers incredible acoustic transparency, thanks to unique 800 Series Diamond features such as our Continuum cone and augmented Matrix bracing system. So while its looks may be conventional, its performance is anything but.

Technical specifications

Technical features	Diamond tweeter Continuum cone FST™ Aerofoil cone bass units Flowport™ Optimised matrix Solid body tweeter	
Description	3-way vented-box system	
Drive units	1x ø25mm (1 in) diamond dome high-frequency 1x ø130mm (5 in) Continuum cone FST™ midrange 2x ø165mm (6.5 in) Aerofoil cone bass units	
Frequency range	20Hz to 35kHz	
Frequency response (+/-3dB from reference axis)	24Hz to 28kHz	
Sensitivity (on axis at 2.83Vrms)	89dB SPL (2.83Vrms at 1m)	
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m on axis) <1 % 70Hz - 20kHz <0.3% 120Hz - 20kHz	
Nominal impedance	8Ω (minimum 3.0Ω)	
Recommended amplifier power	50W - 200W into 8Ω on unclipped programme	
Max. recommended cable impedance	0.1Ω	
Dimensions Height: Width: Depth:	238mm (9.4 in)	
Net weight	33kg (73lb)	
Finishes	Cabinet Real wood veneers: Rosenut Painted finish: Gloss Black Satin White	Grille Black Black Grey

Bowers&Wilkins

www.bowers-wilkins.com

Flowport and FST are trademarks of B&W Group Ltd. Copyright © B&W Group Ltd. E&OE